

WiMER2 is the WiMER designed for Fowler/Sylvac users. It collects readings from Fowler/Sylvac instruments with RS232 outputs and transmits data wirelessly via Bluetooth Low Energy to iPhone/iPad/Android/PC.

WiMER2 also powers the connected instrument. No external power supply is needed.

### Key Features

- Dimension: 60 x 45 x 25 mm
- Resolution: 0.001 mm (depending on the instrument)
- Range: 12.7 mm (depending on the instrument)
- Sampling Frequency: 10 Hz
- Wireless Working Range: 10 m (line of sight)
- Working Temperature: 0-50 °C
- Battery: 850 mAh rechargeable
- Charging: 5 VDC USB and 110 VAC



### Applications

- Crankshaft Deflection Test
- Rotor Runout Test
- Bore Measurement
- Surface Profile Test

### Compatible with Fowler Digital Instruments:

- Micrometer 54-815/866/870
- Caliper 54-100(with data output)/110
- Digital Indicator 54-530/562
- More

### Apps Features:

- Free engineering Apps/Software
- Multiple devices simultaneous reading
- Display acquired data in real-time graph
- Continuous or Single Measurement recordings
- Analog rotating dial indicator on screen
- Probe meter with adjustable range
- Pinch, Pan, Max, Min, Average

- TIR (total indicator reading) & threshold/indicator
- Multiple sampling rate options
- Off-line post processing plot and polar plot
- Record data, CSV and SQLite database
- Export via email and Dropbox synchronization
- Quick custom PDF report with results, graphs, image, logo, signature, map and GPS location

